



**NOTES -**

1. CONTACT MATERIAL - POLYETHYLENE, SCREW & TUBE - 304 SS
2. DRIVE MOTOR - 1/2 HP, TENV, 1750 RPM, 90 VA PERMANENT MAGNET DC MOTOR, 56 C-FACE, MODEL No. CDP-3330 OR EQUAL
3. SPEED REDUCER - MODEL #BMQ-818-10-R-56, 10:1 RATIO
4. CONTROLLER - STD. SCR CONTROLLER IN NEMA 4 ENCLOSURE, 115V/1/60HZ. INPUT
5. VIBRATOR - MODEL No. VBM-2/M, 3600 RPM, 115V/1/60HZ.
6. CARBON STEEL SURFACES TO BE PAINTED W/ STD. V.S. WHITE ENAMEL

SCREW SIZE	TUBE OD
1/2"	3/4"
5/8"	7/8"
3/4"	1.050"
1"	1 1/2"
1 1/2"	2"
2"	2 1/2"

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART, FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.

DO NOT SCALE PRINT

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

TOLERANCES:  
 XX = ±.01  
 XXX = ±.005  
 FRACTIONAL = ±1/32"  
 ANGULAR = ±1/2"  
 BREAK SHARP EDGES .005-.015  
 ALL SMALL FILLETS .020-.040R.



**Vibra Screw Incorporated**  
 755 Union Blvd. Totowa, N.J. 07812-2207

TITLE 1/2" THRU 2" AccuFeed FEEDER

STANDARD DIMENSIONS

SCALE 1/4"=1"

CAD FILE NAME N:\FEEDER\SCREW\ACCUFEED\STDASSY\17687

DWG. NO.

AF-17687

REV. NO.

1

REV.	DESCRIPTION	DWN. BY DATE	CHK. BY DATE	APP. BY DATE	ELEC. APP. DATE
1	RELEASED FOR WEBSITE	JYP 5/8/08			