

INLET WITH
FLEX. SLEEVE
RIP-STOP NYLON
& (2) CLAMPS

VENT
W/ SOCK

VIBRATOR MOTOR
DRIVE MOTOR,
REDUCER,
PLATFORM
SCALE

VIBRATING BAFFLE

1 1/2 C.F.
HOPPER

5 C.F.
HOPPER

3 C.F.
HOPPER

STAINLESS STEEL
SCALE TOP

OUTLET WITH
FLEX. SLEEVE
RIP-STOP NYLON
& (2) CLAMPS

(2) JUNCTION
BOXES (FOR
MOTOR & LOAD
CELL FIELD
WIRE CONNECTIONS)

SHIPPING
BLOCKS (4)

24"

"A"

"C"

6"

5 3/8"

18"

9 3/4"

18 5/8"

34 7/8"

42 7/8"

50 7/8"

2 7/16"

SCREW SIZE	DIM "A"	DIM "C"
1"	9"	2 1/4"
1 1/2"	9 1/4"	3"
2"	9 1/2"	3"

REV.	DESCRIPTION	DWN. DATE	CHK. DATE	APP. DATE	ELEC. APP. DATE
S	RELEASED FOR STANDARD	5/25/01			

DO NOT SCALE PRINT
UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
TOLERANCES:
.XX = ±.01
.XXX = ±.005
FRACTIONAL = ±1/32"
ANGULAR = ±1/2"
BREAK SHARP EDGES .005-.015
ALL SMALL FILLETS .020-.04DR.
ALL FINISHED SURFACES 63-125
MICRO INCHES



Vibra Screw Incorporated
755 Union Blvd. Totowa, N.J. 07512-2207

TITLE
1" - 2" LIW FEEDER
SCALE 3/16=1
DWG. NO. **LIW-17962**
REV. NO. **S**

THE RECIPIENT OF THIS DOCUMENT AGREES NOT TO REPRODUCE, COPY, TRANSMIT OR USE THIS DOCUMENT AND/OR THE INFORMATION CONTAINED IN THIS DOCUMENT IN WHOLE OR IN PART FOR ANY PURPOSE, EXCEPT WITH THE WRITTEN PERMISSION OF VIBRA SCREW INCORPORATED.